

KENWOOD

Listen to the Future

NEXEDGE™

NX-200/300

NEXEDGE™ VHF/UHF Digital & FM Portable Radios

NXDN™

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (450-520 MHz) Models
- 512 CH-GID / 128 Zones
- 12-Key Keypad Models
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 16-Position Mechanical Selector
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-38GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- Intrinsically Safe Option*
- VGS-1 Voice Guide/Storage Option*

● DIGITAL – GENERAL

- NXDN™ Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- NXDN™ Scrambler
- Status Messaging*
- Remote Stun/Kill*
- Short & Long Data Messages*
- GPS Location with Voice*

● DIGITAL – CONVENTIONAL MODE

- 63 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Priority Monitor ID 1 & 2
- Late Entry
- Broadcast Call
- Remote Group Add*
- Multi-Site IP Network Compatible*

● SCAN TYPES (FM & NXDN™ CONVENTIONAL)

- Single/Multi-Zone Scan
- Conventional Scan
- List Scan
- Dual Priority Scan

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control*

● FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-5
- Operator Selectable Tone

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Short Text Messages
- Power On/Off Status Messages
- Send/Display GPS (KMC-38GPS)
- PTT ID & Emergency GPS Reporting
- Status Message Block GPS Reporting
- VGS-1 GPS Data Storage
- PC Serial Interface

* Some features/options are available in future releases.



Options

■ **KNB-47L**
Li-Ion Battery
(1950mAh)



■ **KNB-48L**
Li-Ion Battery
(2550mAh)

KNB-48L

■ **KSC-32**
Tri-Chemistry Rapid
Rate Charger



■ **KMC-25**
Microphone



■ **KEP-1**
Heavy Duty Earphone



■ **KHS-11BL**
2-Wire Palm Mic
with Earphone



■ **KHS-12BL**
3-Wire Mini Lapel Mic
with Earphone



■ **KHS-14**
Lightweight Single
Muff Headset



■ **KHS-15-OH**
Heavy-duty
Over-the-Head Headset



■ **KRA-22/23**
VHF/UHF Helical Antenna



■ **KRA-26/27**
VHF/UHF Whip Antenna



■ **KBH-11**
Belt Clip (2.5")



All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NX-200	NX-300
GENERAL			
Models	Basic Model w / 12 key	NX-200K NX-200K2	NX-300K NX-300K3
Frequency Range		136-174 MHz	450-520 MHz
Number of Channels		512	
Zones		128	
Max. Channels per Zone		250	
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
Operating Voltage		7.5V DC ± 20%	
Battery Life (with KNB-48L)	5-5-90 10-10-80	More than 12.5 hours More than 8.5 hours	
Operating Temperature Range		-30° C to +60° C	
Frequency Stability		± 2.0 ppm	± 1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included		
	Radio only	58 x 127.5 x 41.3 mm	
	with KNB-47L	58 x 127.5 x 41.3 mm	
	with KNB-48L	58 x 127.5 x 48.5 mm	
Weight (net)	Radio only	250 g	
	with KNB-47L	375 g	
	with KNB-48L	405 g	

		NX-200	NX-300
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)	0.20 μV 0.25 μV 0.25 μV	
Selectivity	Analog @ 25 kHz Analog @ 12.5 kHz	72 dB 65 dB	
Intermodulation Distortion	Analog	70 dB (±50, 100 kHz)	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 3%	
Audio Output		500 mW / 8 Ω	
TRANSMITTER			
RF Power Output		5 W / 1 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz Analog @ 12.5 kHz	45 dB 40 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync™ is a registered trademark of Kenwood Corporation.
LTR™ is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows™ is a registered trademark of Microsoft Corporation.
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54			
	IP55			

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

KENWOOD CORPORATION

2967-3, Ishikawa-Cho, Hachioji-Shi, Tokyo 192-8525, Japan

global communications

Reg. No. 1987/003508/07
Highway Business Park, Park Street, Rooihuiskraal, Centurion
P.O. Box 27, The Reeds 0061, PRETORIA, RSA
Tel: +27 12 621 0400 Fax: +27 12 661 0388
e-mail: kenwood@globalcomms.co.za
Home page: www.globalcomms.co.za



Listen to the Future

YOUR LOCAL DEALER

